



PD660

Digital-Analog Radio



Digital & Analog
Dual-Mode
Communication



Ergonomic Design
with Durable Materials



TDMA Dual-Slot,
Double Efficiency



Crystal-Clear Audio,
Ø40mm Speaker




5W High Power Output,
Strong Penetration



Rugged & Reliable,
IP55 Protection

SCENARIOS



Hospitality



Commercial Centers



Emergency Response



Security



Logistics



Sports Events

PRODUCT PARAMETERS



HARDWARE

Frequency Range	VHF: 136-174MHz, UHF: 400-480MHz
Channel Capacity	1024
Channel Spacing	25KHz/12.5KHz
Output Power	UHF: 2W/4W, VHF: 2W/5W
Antenna Impedance	50Ω
Microphone Impedance	2.2kΩ
Bluetooth	Customizable
USB	Type-C
Interface	K-port
Speaker	Ø40mm, 8Ω 2W
Battery	1,500mAh
Working Time	8h
Standby Time	20h
Dimension	125*60*37mm (without Belt Clip and Antenna)
Weight	233.5g
Working Temperature	-20°C ~ +60°C
Storage Temperature	-40°C ~ +75°C



CERTIFICATION

Drop	1.5m
Ingress Protection	IP55
Certification	CE/FCC/ROHS



TRANSMITTER (Standard:EIA-RS 316B)

Modulation Type	Analog: 11KΦF3E@12.5 kHz / 16KΦF3E@25kHz Digital: 7K60FXD (12.5kHz Data), 7K60FXW (12.5kHz Voice & Data)
Frequency Stability	±0.5ppm
Modulation Limiting	±2.5kHz@12.5kHz, ±5.0kHz@25kHz
FM Hum & Noise	≥45dB@12.5kHz, ≥50dB@25kHz
Audio Distortion	≤3%
Audio Response	+1~-3dB
Spurious Emissions	≤-36dBm@<1GHz, ≤-30dBm@>1GHz
Adjacent Channel Power	60dB
Digital Vocoder	AMBE+2™
Digital Protocol	ETSI TS 102 361-1, -2, -3



RECEIVER (Standard:EIA-RS 316B)

Sensitivity	Analog (12dB SINAD): 0.16μV / -123dBm Digital (1% BER): 0.25μV / -119dBm
Intermodulation	60dB
Adjacent Channel Selectivity	60dB
Co-channel Rejection	-8dB
Blocking	85dB
Rated Audio Power Output	2W
Audio Response	+1~-3dB
Audio Distortion	≤3%
Signal-to-Noise Ratio	≥40dB@12.5kHz, ≥45dB@25kHz

STANDARD ACCESSORIES



OPTIONAL ACCESSORIES



Inrico Technologies Co., Ltd.

Tel: +86 755 8327 3589 Email: sales@inricosolutions.com www.inricosolutions.com
12F, Block B, Bldg 12, Shenzhen Bay Science and Technology Ecological Park, Nanshan District, Shenzhen, China

Inrico is dedicated to providing professional communication solutions to global users with quality & efficiency and enrich global wireless communications ecosystem. For more information about our products and solutions, please contact us or visit www.inricosolutions.com.

Inrico and stylized Inrico logo are trademarks of Inrico Technologies Co., Ltd. All rights reserved

